

Fitting Instructions – Atlantic DIN Bathlock/Atlantic DIN Radius Bathlock

ALKDINED60(finish)/ALKDINRED60(finish)

Date Modified: 19/02/2024

Last modified by: Brock Hutchins

For best results when fitting Atlantic UK DIN Dead lock follow these instructions.

Atlantic recommends this product is fitted by a joiner.

Before beginning installation, check the product is as required/ordered.

Separate out all components supplied as follows:

- DIN Euro Deadlock
- 3no. Machine Screws for holding face plate.
- Faceplate
- Keep
- 5no. Wood Screws
- Dust Box

- 1) Mark out the desired location of the DIN Lock on the door
- 2) Using the faceplate, mark out and drill/router out for the fore-end, making sure you account for both the faceplate and the fore-end that is attached to the lock body.
- 3) Drill out for the body, this is standard across all DIN locks and latches, ensuring that there is clearance for the dead lock to sit all the way in.
- 4) Once this fits properly, use 2no of the wood screws included and fasten the lock into the mortice you have drilled out.
- 5) Mark out and drill out for the Euro Profile hole is also a 60mm backset and 55mm below the centerline.
- 6) Using the 3no machine screws, attach the fore-end to the main body of the lock, and test the deadbolt tongue for function.
- 7) Using the Deadbolt tongue, mark out for the keep on the rebate of the door frame.

- 8) Using the keep, mark out where you will need to drill/router out for this, as well as the dust box.
- 9) Drill/router out for the keep and dust box, and then test for fit. Once fitting correctly, fix in place using 3no. of the wood screws provided.
- 10) Once you have fitted the Euro Cylinder and escutcheon, check for function and adjust as needed.