

Senza Pari Lever on Square Rose

Date Modified: 20/09/2022

Last modified by: Brock Hutchins

For best results when fixing Senza Pari levers on square rose, follow these instructions.

1. Take the lever out of the packaging and remove the fixing plate from the left-hand lever using the included Allen key and place lever in a safe place
2. Fit latch in desired location – latch not included.
3. Mark out desired location of the lever on the door, and then using the right-hand lever and spindle to mark out the position of the lugs on the door
4. Using an appropriate drill bit, drill all the way through the door for the lugs, ensuring you stay square and level to the door
 - a. Pro tip – go halfway through the door and then come back the other way with the drill, leaving a cleaner hole on both sides.
5. When you have drilled the holes for the lugs, place right hand lever and spindle on the correct side of the door, and push the lever tight to the door
6. With the right-handed lever in place, take the fixing plate and push into the holes previously made, and then fix the plate to the right-hand lever using the bolt through fixings provided
 - a. Pro tip – if you need to cut the bolts down, use an angle grinder and thread up an appropriately sized nut beyond the point you need to cut, and then when finished your cut, unthread the nut all the way off, it will clean up any disfigurement of the threads from cutting.
7. Place the left-hand lever onto the fixing plate top first, and then drop the bottom into place, and then using the smaller of the 2 Allen keys provided, tighten up the grub screw on the underside of the rose.
8. Using the 2 grub screws provided, as well as the larger Allen key, thread the grub screws into the tapped holes on the levers, tightening one up all the way
9. Tighten the 2nd grub screw all the way, ensuring that the lever is pushed tight against the door.
10. Test levers to ensure correct operation of both levers and latch.