

## ECO50(finish) ECO CREST


Product Code	ECO50(finish)
Product Name	ECO Crest Lever
Product Description	Crest Lever on Round Rose
Product Base Material	Aluminium Lever on Zinc Alloy Screw on Rose
Available Finishes	Satin Chrome/Polished Chrome (SCPC)

Other Information	To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will damage the applied finish. Supplied 2 x Bolt through Fixing, Wood Screws, 8 mm x 8 mm x 100 mm Split Spindle, 2 x Loctite coated Grub Screws & Allen Key. Bolt through Fixing and Grub Screws must be used. 10 Year Mechanical Guarantee subject to fitting requirements.
Matching WC Turn:	S3WCR(finish)
Matching ESC:	Key: S3ESCKR(finish) Euro: S3ESCER(finish)

### Dimensions

ECO50 Lever Dimensions:

- A: 51mm
- B: 134mm
- C: 10mm
- D: 68mm



### Product Image



Product Finish Pictured: Satin Chrome/Polished Chrome

### Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

These latches have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposit, try using a PH neutral soap on a soft cloth, then remove soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these locks. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery. Atlantic UK retain the right to send items away for chemical testing to analyse if the product has come into contact with any abrasive or chemical substance before issuing replacements.

Please be aware that environments where there are high concentrations of chemicals in the air, for example from use of low quality paint or corrosive agents, corrosion and damage may occur to the surface of the lock. Locks should therefore not be fitted in such environments, until the high concentration of chemicals in the air have subsided.

*the finish matters*